

BID 122120WA – Charging Stations Electrical Equipment

Power Strip - 6 Outlet - 6ft Cord - White



Specifications

OUTPUT

Frequency Compatibility 60 Hz

Output Receptacles (6) 5-15R

Output (Watts) 1875

Circuit Breaker (amps) 15

Overload Protection 15A circuit breaker

Outlet Orientation Single row of 6

INPUT

Nominal Input Voltage(s) Supported 120V AC

Recommended Electrical Service 15A 120V

Input Connection Type NEMA 5-15P

Input Cord Length (ft.) 6

Input Cord Length (m) 1.83

Input Cord Gauge Type SJT 14AWG

Voltage Compatibility (VAC) 120

USER INTERFACE, ALERTS & CONTROLS

Switches Illuminated on/off switch controls power to all outlets

Dimensions

Shipping Dimensions (hwd/in.) 11.03 x 4.17 x 1.57

Shipping Dimensions (hwd/cm) 28.02 x 10.59 x 3.99

Shipping Weight (lbs.) .86

Shipping Weight (kg) 0.39

Unit Dimensions (hwd/in.) 9.5 x 1.5 x 1.5

Unit Dimensions (hwd/cm) 23.3 x 3.81 x 3.81

Unit Weight (lbs.) .81

Unit Weight (kg) 0.37

6 – Outlet Grounded Tap -Wall Adapter Gray



Specifications

Dimensions

Product Depth (in.) 2.50

Product Height (in.) 7.50

Product Length (in.) 2.50

Product Width (in.) 4.55

Details

Color Family - Gray

Commercial/Residential - Residential

Cord Included No

Electrical Product Type - Electrical Cords & Cord Management

Features

Grounded

Indoor/Outdoor - Indoor

Maximum Amperage (amps) 15

Maximum Current 1875

Number of Outlets 6

Number of USB Ports 0

On Indicator Light No

Product Weight (oz.) 7.52 oz

Resettable circuit breaker Yes

Voltage (volts) 125

Wired or Wireless Wireless

PRICING SCHEDULE

Item	Quantity Needed	Item Cost Each	Total Cost
Power Strip	9683	\$	\$
Wall Adapter	4841	\$	\$